



Auto4 Ltd
 Unit 4a, Park Lane Business Court, Park Lane,
 Kirkby in Ashfield, Nottinghamshire, NG17 9GU
 T:+44(0)1623 727360 F:+44(0)1623 721950
 sales@auto4.co.uk www.auto4.co.uk
 Orderline:0845 0770 190 Automotive Equipment,
 Tools and Consumables

SAFETY DATA SHEET

Page 1 of 3

202180 PENETRATING OIL

Revision 0
 Revision date

I. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name PENETRATING OIL
Company Auto4
 Unit 4a
 Park Lane Business Court
 Park Lane
 Kirkby-in-Ashfield
 Nottingham
 Nottinghamshire
 NG17 9GU
sales@auto4.co.uk
www.auto4.co.uk
Telephone 01623 727360
Fax 01623 721950
Product code 202180

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients	Conc.	CAS	EINECS	Symbols/Risk phrases
Kerosine - unspecified - distillates (petroleum), hydrotreated light	90 - 100%	64742-47-8	265-149-8	Xn; R65
Special Boiling Point Spirit 100/140	1 - 10%	64742-49-0	265-151-9	F;R11 Xi;R38 N;R51/53 Xn;R65

3. HAZARDS IDENTIFICATION

Main hazards Harmful: may cause lung damage if swallowed.

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.

Ingestion Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

5. FIRE FIGHTING MEASURES

Extinguishing media Use as appropriate: carbon dioxide (CO2), dry chemical, foam.

Fire hazards Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Self-contained breathing apparatus. Wear protective clothing.

PENETRATING OIL

Revision 0
Revision date

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Colourless.
Odour	Slight.
Water solubility	miscible in water.

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

Toxicological information	No data is available on this product.
----------------------------------	---------------------------------------

Special Boiling Point Spirit 100/140

Oral Rat LD50 = >2000mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity	No data is available on this product.
--------------------	---------------------------------------

13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
----------------------------	---

PENETRATING OIL

Revision 0
Revision date

14. TRANSPORT INFORMATION

ADR/RID

UN 1223	Packing group III
Class 3	Hazard ID 30
Proper Shipping Name KEROSENE BASED PENETRATING OIL.	

IMDG

UN 1223	Packing group III
Class 3	Marine pollutant NO
EmS Code F-E S-E	

IATA

UN 1223	Packing group III
Class 3	Subsidiary risk -
Packing Instruction (Cargo) 310	Maximum quantity 220 L
Packing Instruction (Passenger) 309	Maximum quantity 60 L

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols Xn - Harmful



Risk phrases R65 - Harmful: may cause lung damage if swallowed.

Safety phrases S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16. OTHER INFORMATION

Text of risk phrases in Section 2 R11 - Highly flammable.
R38 - Irritating to skin.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 - Harmful: may cause lung damage if swallowed.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. As the application of products is outside our control, the information is given without legal responsibility. Customers should test under their own conditions to ensure the products are suitable for their own requirements.